



The gas hob with front control - for a comfortable regulation of the 5 gas burners.

- $\sqrt{\mbox{ Pan Supports}}$ continuous cast-iron pan supports for maximum stability and cooking convenience.
- $\sqrt{\mbox{ Wok Burner}}$ powerful cooking at up to 3.3 kW.
- $\sqrt{\,}$ Sword Knobs a better feel and easier to operate, the new knob in an attractive design.
- $\sqrt{\ }$ Stainless steel surface elegant and sophisticated design.

Features

Technical Data

Product name/family : gas hob w integrated controls

Construction type : Built-in

Energy input : Gas

Total number of positions that can be used at the same time : 5

Type of control setting devices : sword knobs

Required niche size for installation (HxWxD) : 45 x 560-562 x

480-492 mm

Width of the appliance : 750 $\,$ mm Dimensions : 45 x 750 x 520 $\,$ mm

Dimensions of the packed product (HxWxD) : $145 \times 793 \times 597$ mm

Net weight : 12.963 kg Gross weight : 14.5 kg

Residual heat indicator: without Location of control panel: Hob front Basic surface material: Stainless steel Color of surface: Stainless steel Color of frame: Stainless steel Approval certificates: not relevant Length of electrical supply cord: 150 cm

EAN code : 4242004234289 Electrical connection rating : 1 W Gas connection rating : 10800 W

Fuse protection : 3 A Voltage : 220-240 V Frequency : 50; 60 Hz





Features

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet

Usage convenience

- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 5 burner hob
- Left front: Economy burner up to 1 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Center front: Wok burner up to 3.3 KW (depending on gas type)
- Right rear: High speed burner up to 3 KW (depending on gas type)
- Right front: Standard burner up to 1.75 KW (depending on gas type)

Safety

• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU)
 Liquid gas G30,31 28-30/37mbar
 Natural gas L 25 mbar (NL)
 Liquid gas G30 37 mbar (PL)
 Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- \bullet Dimensions of the product (HxWxD mm): 53 x 750 x 520
- \bullet Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1.5 m
- Connected load: 10.8 KW



Dimensioned drawings



