


KS110BLE

Hood, Decorative wall hood, Universal, Black, 110 cm, B

INTENSIVE EXTRACTION

A powerful intensive speed can be selected when quick extraction is needed, whether you're creating a sizzling stir fry or preparing an aromatic curry, even the strongest cooking odours will be removed in no time.



TYPE

Product family: Hood • Hood Type: Decorative wall hood • Hood width: 110 cm • Extraction: Expulsion • Electronic control: Yes •

EAN code: 8017709201845

AESTHETICS

Colour: Black • Aesthetics: Universal • Design: T flat • Material: Painted material • Type of steel: Brushed

PROGRAMME / FUNCTIONS

No. of speeds: 3 • Intensive speed: Yes • Time-setting options: Automatic switch-off

CONTROLS

Control setting: Electronic buttons

TECHNICAL FEATURES

No. of lights: 2 • Light type: LED • Light power: 1 W • Light color temperature scale (°K): 4000 °K • Free outlet maximum capacity: 800 m³/h • Motor power: 275 W • No. of filters: 3 • Anti-grease filters: Aluminium • Filter replacement indicator: Yes • Minimum distance from GAS hob: 750 mm • Vent outlet: 150 mm • Minimum distance from ELECTRIC hob: 650 mm • Non return valve: Yes

PERFORMANCE / ENERGY LABEL

Energy efficiency class (EEC): B • Fluid Dynamic Efficiency class (FDEC): B • Grease Filtering Efficiency Class (GFEC): C • Lighting Efficiency Class (LEC): A • Annual Efficiency Consumption (AEChood): 62 kWh/year • Fluid Dynamic Efficiency (FDE): 27.9 • Lighting Efficiency (LE): 84.1 lux/W • Grease Filtering Efficiency (GFE): 78.7 % • Air flow at minimum speed (Qmin): 295 m³/h • Maximum extraction rate: 513 m³/h • Intensive extraction rate: 702 m³/h • Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 51 dB(A) • Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 64 dB(A) • Airborne acoustical A-weighted sound power emission at boost speed (SPEboost): 72 dB(A) • Power consumption in stand-by mode (Ps): 0.49 W • Time increase factor (F): 1.00 • Energy Efficiency Index per first cavity: 58.2 • Measured air flow rate at best efficiency point (Qbep): 373 m³/h • Measured air pressure at best efficiency point (Qbep): 430 Pa • Measured electric power input at best efficiency point (Wbep): 160 W • Normal Power of the light system (Wl): 2 W • Average illumination of the light on the cooking surface (Emiddle): 370 lux • Sound power level at highest setting (Lwa): 64 dB(A)

ELECTRICAL CONNECTION

Nominal power: 278 W • Voltage: 220-240 V • Frequency (Hz): 50-60 Hz • Power supply cable length: 1000 mm

SPEED 1

Extraction rate IEC 61591: 295 m³/h • Noise level IEC 60704-2-13: 51 dB(A) • Power: 207 W

SPEED 2

Extraction rate IEC 61591: 395 m³/h • Noise level IEC 60704-2-13: 58 dB(A) • Power: 236 W

SPEED 3

Extraction rate IEC 61591: 513 m³/h • Noise level IEC 60704-2-13: 64 dB(A) • Power: 250 W

INTENSIVE SPEED

Extraction rate (IEC 61591): 702 m³/h • Noise level IEC 60704-2-13: 72 dB(A) • Power: 314 W

LOGISTIC INFORMATION

Dimensions of the product (mm): 1142x1100x500 • Width: 1100 mm • Depth (mm): 500 mm • Product Height (mm): 1142 mm

OPTIONAL

FLT4: Charcoal filter kit, HoodsKITALLFC: Charcoal filter, Hoods

