

iQ300, Wall-mounted cooker hood, 60 cm, clear glass LC67AFM50B



B



Glass design extractor hood with a high extraction rate.

- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ touchControl: quickly and easily manage the power levels and the LED light
- ✓ Fast-acting extraction for sudden bursts of steam - Intensive Setting

Features

Technical Data

Typology : Chimney
 Approval certificates : CE, VDE
 Length of electrical supply cord (cm) : 130
 Height of the chimney (mm) : 576-897/576-1007
 Height of product, without chimney (mm) : 50
 Minimum distance above an electric hob : 550
 Minimum distance above a gas hob : 650
 Net weight (kg) : 14.811
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 474
 Boost position output recirculating (m³/h) : 499
 Maximum output recirculating air (m³/h) : 404
 Boost position air extraction (m³/h) : 715
 Number of lights (Stck) : 2
 Noise level (dB(A) re 1 pW) : 67
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable stainless steel
 EAN code : 4242003800447
 Connection rating (W) : 255
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 50; 60
 Plug type : GB plug
 Installation type : Wall-mounted

Optional accessories

LZ50661 : Backboard 60 x 72 cm , LZ50660 : Backboard 60 x 65 cm ,
 LZ31XXB16 : Clean Air Plus odor filter (replacement) , LZ12350 :
 Chimney extension 1500 mm , LZ12250 : Chimney extension
 1000 mm , LZ11FXD51 : Long Life recirculation kit external ,
 LZ11FXC56 : Clean Air Plus recirc. kit external , LZ11DXI16 : Clean
 Air Plus recirculation kit , LZ10FXJ00 : Long Life recirculation kit ,
 LZ10DXU00 : Standard recirculation kit , LZ10DXA00 : Standard odor
 filter (replacement) , LZ00XXP00 : Long Life odor filter (replacement)



4 242003 800447

iQ300, Wall-mounted cooker hood, 60 cm, clear glass LC67AFM50B

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 474 m³/h
- Intensive 715 m³/h
- Noise max. Normal Level: Noise, max. speed in normal us: 67 dB dB*

Features

- touchControl for extractor speeds and light
- touchControl with Electronic display
- 3 x power levels plus intensive setting
- Twin channel high performance fan motor
- 2 x 1.5W LED
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 1 x metal grease filter cassette
- Steel filter cover
- Installation: wall

Design

- Chimney hood
- Electronic control

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction a recirculating kit or a CleanAir recirculation kit (accessory) is needed
- Max. extraction rate: 715 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 67 dB(A) re 1 pW
- Intensive: 74 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode:
- Max. normal use: 404 m³/h
- Intensive: 499 m³/h
- Noise level in recirculation mode:
- Max. normal use: 72 dB(A) re 1 pW
- Intensive: 76 dB(A) re 1 pW
- Power rating: 255 W
- Light Intensity: 276 lux
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 617-947 x 600 x 488 mm
- Dimensions recirculating, chimney (HxWxD): 617-1057 x 600 x 488 mm
-
- Dimensions recirculating with CleanAir module (HxWxD):
- 686 x 600 x 488 mm - mounting with outer chimney
- 815-1145 x 600 x 488 mm - mounting with telescopic chimney
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 57.7 kWh/year*

Optional accessories

- Recirculating kit LZ12350

* In accordance with the EU-Regulation No 65/2014

iQ300, Wall-mounted cooker hood, 60 cm, clear glass LC67AFM50B

Dimensioned drawings

