

**iQ500, Canopy cooker hood, 70 cm,
Stainless steel
LB78574GB**

C

**Optional accessories**

LZ55750	Standard recirculation kit
LZ55651	Standard odor filter (replacement)
LZ11IXC16	Clean Air Plus recirc. kit external
LZ11IXB16	Clean Air Plus odor filter (replacement)
LZ11ITD11	Long Life recirculation kit external
LZ10ITP00	

The powerful canopy cooker hood is concealed in a unit above the hob.

- ✓ LED lights: for optimal visibility and ambience while cooking.
- ✓ Fast-acting extraction for sudden bursts of steam - Intensive Setting

Features**Technical Data**

Typology : Traditional
Approval certificates : CE, VDE
Length of electrical supply cord (cm) : 150
Required niche size for installation (HxWxD) : 418mm x 676.0mm x 264mm
Minimum distance above an electric hob : 500
Minimum distance above a gas hob : 650
Net weight (kg) : 8.963
Type of control : Electronic
Maximum output air extraction (m³/h) : 630
Boost position output recirculating (m³/h) : 664
Maximum output recirculating air (m³/h) : 571
Boost position air extraction (m³/h) : 730
Number of lights (Stck) : 2
Noise level (dB(A) re 1 pW) : 66
Diameter of air outlet (mm) : 120 / 150
Grease filter material : Washable aluminium
EAN code : 4242003686263
Connection rating (W) : 277
Current (A) : 3
Voltage (V) : 220-240
Frequency (Hz) : 50
Plug type : GB plug
Installation type : Built-in



4 242003 686263

iQ500, Canopy cooker hood, 70 cm, Stainless steel LB78574GB

Features

Key Information

- Soft touch button control for extractor speeds and light
- 3 x power levels plus intensive setting
- Automatic intensive revert (6mins)
- 2 x 1W LED lights
- 2 x metal grease filter cassettes
- Steel filter cover, Steel filter cover
- Rim ventilation

Design

- 70 cm wide
- Stainless Steel
- Installation: Cabinet
- Electronic control via Soft touch button control
- White electronic display

Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
- max. Normal use 630 m³/h
- Intensive 730 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
- Max. normal use: 66 dB(A) re 1 pW
- Intensive: 69 dB(A) re 1 pW
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
- Extraction rate in recirculation mode:
- Max. normal use: 571 m³/h
- Intensive: 664 m³/h
- Noise level in recirculation mode:
- Max. normal use: 72 dB(A) re 1 pW
- Intensive: 75 dB(A) re 1 pW
- Power rating: 277 W
- Light Intensity: 244 lux
- Colour Temperature: 4000 K
- Dimensions (WxD): 700 x 300 mm
- Built-in dimensions (HxWxD): 418 x 676 x 264 mm
- Dimensions exhaust air (HxWxD): 418-418 x 700 x 300 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Average Energy Consumption: 104.2 kWh/year*
- Energy Efficiency Class: C (at a range of energy efficiency classes from A+++ to D)
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: D*

* In accordance with the EU-Regulation No 65/2014

iQ500, Canopy cooker hood, 70 cm, Stainless steel LB78574GB

Dimensioned drawings

