







Ontional accessories

Z9410X1 Stainless Steel roaster with glas lidZ9415X1 Steaming Rack for Stainless Steel roaste

Z9416X2 Griddle Plate
Z9417X2 Teppan Yaki (large)
Z943SE0 Set of 2 pots and 1 pan

FlexInduction hob with TouchControl.

- $\sqrt{}$ Touch Control Control your hob with a simple touch.
- $\sqrt{\mbox{ Flex Induction}}$ Your hob detects and heats your individual cookware.
- $\sqrt{}$ Power Boost An extra surge of heat when you need fast results.
- $\sqrt{\,}$ Induction the heat is generated directly in the cookware for precise cooking that stops when power is off.

Features

Technical Data

Product name/family: Cooking zone ceramic

Construction type : Built-in Energy input : Electric

Total number of positions that can be used at the same time : 5 Required niche size for installation (HxWxD) : $51 \times 750-750 \times 10^{-2}$

490-500 mm

Width of the appliance : 802 mm Dimensions : $51 \times 802 \times 522 \text{ mm}$

Dimensions of the packed product (HxWxD) : 126 x 953 x 603 $\,$ mm $\,$

Net weight : 16.790 kg Gross weight : 18.2 kg

Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Ceramic Color of surface : Black

Approval certificates : AENOR, CE

Length of electrical supply cord : 110 cm

EAN code: 4242004195788

Electrical connection rating: 7400 W

Voltage: 220-240 V Frequency: 50; 60 Hz





Features

Design

- Bevelled front edge
- 80 cm: space for 5 pots or pans.

Flexibility of cooking zones

- Flex Induction: use cookware of any shape or size anywhere within the 40cm long zone.
- Cooking zone front left: 180 mm, 1.8 KW (max. power 3.1 KW)
- Cooking zone rear left: 145 mm, 1.4 KW (max. power 2.2 KW)
- Cooking zone middle: 240 mm, 2.2 KW (max. power 3.7 KW)
- Cooking zone rear right: 210 mm, 200 mm, 2.2 KW (max power 3.7 KW)
- Cooking zone front right: 210 mm, 200 mm, 2.2 KW (max. power 3.7 KW)

Usage convenience

- Touch control: control the power with imprinted +/- touch buttons.
- Variable 17-stage power settings for each zone: precisely adapt the heat with 17 power levels (9 main levels and 8 intermediate levels).
- Keep warm function: keep dishes warm at preset low power level.
- Timer with automatic shut off for all zones
 : switches off the cooking zone at the end of the time set (e.g. for boiled eggs).
- LED timer for each zone with switch off function and acoustic signal
- : an alarm sounds at the end of the time set (e.g. for pasta).

Time saving & efficiency

- Power Boost function for all zones
 : boil water faster thanks to 50% more energy than at the highest standard level.
- QuickStart function: when switching on, the hob automatically selects the cooking zone with cookware (when placed on a zone whilst the hob is off).
- ReStart function: in case of unintentional switch-off, this feature restores all previous settings by switching on the hob again within 4 seconds.

Safety

- 2 stage residual heat indicators: indicates which cooking zones are still hot or warm.
- Control panel lock: prevent unintended activation of the hob.
- Control panel suspension: wipe overboiled liquids without unintentionally changing settings (blocking all touch buttons for 30 seconds).
- \bullet Main switch: switch off all cooking zones at the touch of a button.
- Safety cut out facility: for safety reasons, heating stops after a preset time if not used (possible to customise).
- Energy consumption display: shows the electricity consumption of the last cooking process.

Installation

- Dimensions of the product (HxWxD mm): 51 x 802 x 522
- Required niche size for installation (HxWxD mm): 51 x 750 x (490 500)
- Min. worktop thickness: 16 mm
- Connected load: 7.4 KW
- 4.6kW power output (20A); current management options for 16A, 13A or 10A connection: limit the maximum power if needed (depends on fuse protection of electric installation).
- Power cord: 1.1 m, Cable included in packaging



