





The gas hob with a stainless-steel surface design and adjustable FlameSelect.

- $\sqrt{\text{FlameSelect}^{\text{@}}}$ Gain ultimate control of your flame.
- $\sqrt{\,}$ Pan Supports continuous cast-iron pan supports for maximum stability and cooking convenience.
- $\sqrt{\mbox{ Wok Burner}}$ powerful cooking at up to 3.5 kW.
- $\sqrt{\,}$ Sword Knobs a better feel and easier to operate, the new knob in an attractive design.
- $\sqrt{\ }$ Stainless steel surface elegant and sophisticated design.

Features

Technical Data

Product name/family : gas hob w integrated controls

Construction type : Built-in

Energy input : Gas

Total number of positions that can be used at the same time: 4

Type of control setting devices : sword knobs

Required niche size for installation (HxWxD) : $45 \times 560-562 \times 10^{-2}$

480-492 mm

Width of the appliance : 582 mm Dimensions : 45 x 582 x 520 mm

Dimensions of the packed product (HxWxD) : $141 \times 651 \times 578 \text{ mm}$

Net weight: 11.431 kg Gross weight: 12.3 kg

Residual heat indicator: without Location of control panel: Hob front Basic surface material: Stainless steel Color of surface: Stainless steel Color of frame: Stainless steel Approval certificates: CE, Eurasian Length of electrical supply cord: 100 cm

EAN code : 4242004203438 Electrical connection rating : 1 W Gas connection rating : 8000 W

Fuse protection : 3 A Voltage : 220-240 V Frequency : 60; 50 Hz





Features

Design

- Stainless steel surface
- black cast iron pan supports with protective rubber feet

Usage convenience

- FlameSelect with 9 steps: precisely control and adjust the flame in nine defined levels.
- Design co-ordinated control dials: easily access dials in front with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner hob
- Left front: Standard burner up to 1.75 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: WOK burner up to 3.5 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety


• Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE) NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 53 x 582 x 520
- \bullet Required niche size for installation (HxWxD mm) : 45 x 560 x (480 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 8 KW

Dimensioned drawings





** Minimum distance from the hob cut-out to the wall

** Position of gas connection in the cut-out

*** With fitted oven underneath, possibly more; see space requirements for the oven

measurements in mm